

JIALIFT®



www.jialift.com.au

CL1636GA Full Electric Stacker

CE

- 1600kg Capacity; Max Lifting Height - 3600mm
- Walk-behind operate no license required
- Safe, reliable, sustainable and low maintenance

Full Electric Walkie Stacker (1600kg/3600mm)

- Imported CURTIS AC controller and MOSFETS drive have functions of the step-less speed regulating and reverse braking.
- Perfect temperature protection and compensation functions ensure thermal protection and stable output.
- The advanced vertical AC drive system. The motor can get more energy and greater braking torque to make it more powerful and better in acceleration.
- The hydraulic power unit is with compact structure, small size, light weight, high efficiency, no leaks, reliable performance.
- The whole series use H type steel, which is especially for forklifts, for mast. H type steel is with good plasticity.

Standard Equipment:

Also Included in our Offer: Battery and Charger

Warranty: 5 Years refer to the JIALIFT warranty terms and conditions



JIALIFT AUSTRALIA PTY LTD

Call Us: 1300 000 168 Email: sales@jialift.com.au

www.jialift.com.au

Distinguishing mark		
Model designation		CL1636GA
Load capacity	kg	1600
Load capacity on max. Height	kg	900
Max lifting height	mm	3600
Load center distance	mm	600
Weight		
Service weight	kg	1065
Dimensions		
Fork length	mm	1150
Single fork width	mm	180
Overall fork width	mm	570/695
Lowered fork height	mm	86
Fixed leg length	mm	903
Single fixed leg width	mm	124
Inside width between fixed legs	mm	266/391
Outside width between fixed legs	mm	514/639
Turning radius	mm	1570
Aisle width for pallets 1000 × 1200 crossways	mm	2452
Aisle width for pallets 800 × 1200 lengthways	mm	2432
Overall length	mm	2040(2460)
Overall width	mm	808
Lowered mast height	mm	2291
Extended mast height	mm	4008
Types, Chassis		
Front wheel size, number	mm	80x70, 4
Rear wheel size, number	mm	250x75, 1
Balance wheel size, number	mm	115x55, 2
Performance data		
Driving speed, laden/ unladen	km/ h	5.2/5.5
Lifting speed, laden/ unladen	mm/ s	80/210
Lowering speed, laden/ unladen	mm/ s	152/160
Electric-engine		
Drive motor rating	kW	1.5
Lift motor rating	kW	3
The charger		24V/30A
Battery voltage/nominal capacity		24V/210AH
Battery dimensions	mm	790/210/458
Working time of fully charged	h	5

