

CL1020/30/35J

Full Electric Walkie Stacker

- Walk-behind operate no license required
- Control panel: Red Stop Bottom, Key Switch and Battery Indicator on the Right. In-built charger on the Left
- The in-built charger is the single phase (wall plug) that can be easily charged
- The side-driven design effectively reduces the size of the operation channel.
- With a small turning radius, this stacker is suitable for narrow spaces.
- Though it is an economical power stacker, it is still equipped with a high-power and high-performance lifting pump station, which ensures the goods lifting.
- Adjustable driving speed switch
- The turtle speed switch on the handle makes low-speed control more precise.
- Germany imported waterproof micro-switches are applied in cold, damp, dusty and other harsh environments.
- YONGCI motor drive system is small in size, lightweight, low loss and high in efficiency.



CL1020/30/35J

Manufacturer's Data and Technical Characteristics				
Manufacturer	JIALIFT®			
Model designation	sku	CL1020J	CL1030J	CL1035J
Load capacity	kg	1000		
Load capacity on max. Height	kg	800	700	600
Max lifting height	mm	2000	3000	3500
Load center distance	mm	600		
Weight				
Service weight	kg	441	465	485
Dimensions				
Fork length	mm	1150		
Single fork width	mm	160		
Overall fork width	mm	570/695		
Lowered fork height	mm	86		
Fixed leg length	mm	928		
Single fixed leg width	mm	124		
Inside width between fixed legs	mm	262/387		
Outside width between fixed legs	mm	534/659		
Turning radius	mm	1336		
Aisle width for pallets 1000 × 1200 crossways	mm	2074		
Aisle width for pallets 800 × 1200 lengthways	mm	2040		
Overall length	mm	1755		
Overall width	mm	795		
Extended mast height	mm	2424	3424	3924
Lowered mast height	mm	1494	1994	2244
Types, Chassis				
Front wheel size, number	mm	ø80x70, 4		
Rear wheel size, number	mm	ø210x70, 1		
Balance wheel size, number	mm	ø115x58, 1		
Performance data				
Driving speed, laden/ unladen	km/ h	4/4.2		
Lifting speed, laden/ unladen	mm/	100/155		
Lowering speed, laden/ unladen	mm/	150/130		
Electric-engine				
Drive motor rating	kW	0.75		
Lift motor rating	kW	2.2		
The controller		24V/90A		
The charger		24V/10A		
Battery voltage/nominal capacity		2x12V/100AH		
Battery dimensions	mm	260/169/215		



CL1020/30/35J

