

HIW2.0/4.0

Full Electric Scissor Lift Table

- The tried and trusted lift table with sturdy construction.
- Multiple uses such as lifting and lowering materials, level compensation when fitting machines, installations in the conveyor system, etc.
- Compact hydraulic design with all safety components complying with EN1570.
- High-pressure cylinder with dual safety function.
- Hard chrome plated piston rods.
- Lift and lower by easily push buttons to reach the ergonomically correct working height.
- With the emergency switch off and a 3m long control cable.
- The table utilizes a safety bar around the perimeter to sense any foreign objects in which case it will stop the movement instantly
- These tables are normally operated from the factory floor but can be installed in a pit (require eyebolt lifting lugs).
- Driven by an electric motor mounted under the table, which is controlled by a pendant hand controller on a curly cable



HIW2.0/4.0

Manufacturer's Data and Design Characteristics			
Manufacturer	JIALIFT®		
Model designation	sku	HIW2.0	HIW4.0
Load capacity	kg	1000	2000
Min. height	mm	190	220
Max. lifting height	mm	1010	1010
Lifting speed	s	26	40
Lower speed	s	20	30
Weight			
Service weight	kg	220	280
Dimensions			
Platform size	mm	1300x800	1300x800
Electric-engine			
Lift motor	kw	0.75 AC3X380V	0.75 AC3X380V
Pump electric current	L/min	3	3
Oil tank	L	2	3

