

## SPN1020/25/30/35S

### Semi-Electric Walkie Stacker

- Walk-behind operate no license required. Straddle Legs Models suit on Standard Australian Pallet (CHEP)
- Control Panel: Fascia-mounted control panel with raise/lower buttons, emergency stop trigger, battery indicator and hour-meter.
- The in-built charger is single phrase (wall plug) can be easily charged
- Adjustable Fork: Forged forks with an adjustable width. Easy service and maintenance
- Lockable wheel: Wheels: Brake-enabled with 360-degree rotation. Large diameter steered rear wheel for easy movement across any surface
- Electric lift and manual push, easy to control, and environmental efficiency, which is widely used in overhead cargo and pallet moving and stacking.
- Safe and efficient in factories, warehouses, and logistics centres



### SPN1020/25/30/35S

Manufacturer's Data and Technical Characteristics					
Manufacturer	<b>JIALIFT®</b>				
Model designation	sku	SPN1020S	SPN1025S	SPN1030S	SPN1035S
Load capacity	kg	1000			
Load capacity on max. Height	kg	1000	1000	700	500
Max lifting height	mm	2000	2500	3000	3500
Load center distance	mm	600			
Weight					
Service weight	kg	470	485	504	510
Dimensions					
Fork length	mm	1150			
Single fork width	mm	100			
Two forks outside width	mm	210-830			
Lowered fork height	mm	40			
Fixed leg length	mm	1120			
Single fixed leg width	mm	50			
Inner width of two fixed legs	mm	1230			
Outside width of fixed legs	mm	1330			
Turning radius	mm	1350			
Aisle width for pallets 1200 × 1200 crossways	mm	2400			
Overall length	mm	1800			
Overall width	mm	1330			
Extended mast height	mm	2580	3070	3570	4060
Lowered mast height	mm	1580	1820	2080	2330
Types, Chassis					
Front wheel size, number	mm	ø100x26, 4			
Rear wheel size, number	mm	ø180x50, 2			
Electric-engine					
Lift motor rating	kW	1.5			
Lift motor	V	DC 12V			
The charger		12V/20A			
Battery voltage/nominal capacity		12V/120AH			



## SPN1020/25/30/35S

