

JIALIFT®



www.jialift.com.au

CQDH15R-4500

Full Electric Walkie Reach Stacker

CE

- 1350kg Capacity; Max Lifting Height - 4500mm
- Walk-behind operate no license required
- Safe, reliable, sustainable and low maintenance

Full Electric Walkie Reach Stacker (1350kg/4500mm)

- Walk behind operate no licence required. Operation platform have to be removed based on the latest Australian Work Safe Standards
- Compatible on both Standard Australian Close Pallet (CHEP) and Open Pallet
- AC drive system, EPS, Moon walk, ZAPI controller
- Side shifter, Reach, Tilt

Standard Equipment:

Also Included in our Offer: Battery and Charger

Warranty: 5 Years refer to the JIALIFT warranty terms and conditions



JIALIFT AUSTRALIA PTY LTD

Call Us: 1300 000 168 Email: sales@jialift.com.au

46-48 Geddes St, Mulgrave VIC 3170 Open at 8:30 am - 5:30 pm, Monday-Friday



www.jialift.com.au

Distinguishing mark		
Model designation		CQDH15R-4500
Type		Reach (Tilt, Side shifter)
Mast type		Standard 3-stage
Load capacity	kg	1350
Max lifting height	mm	4500
Load center distance	mm	500
Service weight with battery	kg	2420
Battery weight	kg	260 or 320
Dimensions		
Fork length	mm	1070
Single fork width	mm	100
Fork thickness	mm	45
Reach distance	mm	0-500
Load distance centre of drive axle to fork	mm	365
Turning radius	mm	1730
Aisle width for pallets 1000 × 1200 crossways	mm	2630
Aisle width for pallets 800 × 1200 lengthways	mm	2630
Min ground clearance	mm	50
Overall length	mm	2190
Overall width	mm	1240-1600/950
Extended mast height	mm	5570
Lowered mast height	mm	2200
Tyre type Driving wheels/Bearing wheels		PU
Performance data		
Driving speed, laden/ unladen	km/ h	4.8/5
Lifting speed, laden/ unladen	mm/ s	95/120
Lowering speed, laden/ unladen	mm/ s	200/150
Max. gradeability, laden/unladen	%	5/12
Electric engine		
Drive motor rating	kW	1.5
Lift motor rating	kW	4.5
Steering motor rating	kW	0.15
Battery voltage/nominal capacity		24V/320 Ah
Brake	mm	Electromagnetic/Regenerative
Controller		ZAPI