

## **Articulated Forklift MJ20**

- Compared with counterbalanced forklift, pallet positions have increased by 200%. Reach height has increased by 100% (10M), and aisle width has decreased by 45% (1.9M).
- Narrow aisle and high storage capacity
- · Indoors and outdoors using
- High speed driving and high efficient work
- Flexible steering



















Specification			
1	Manufacturer		MiMA
2	Model		MJ
3	Power type		Battery
4	Driving style		Seated
5	Rated load	Q(kg)	2000
6	Load center	C(mm)	600
7	Front overhang	x(mm)	285
8	Wheelbase	y(mm)	1720
9	Service Weight(incl.battery)	kg	8000
10	wheel type		Solid rubber tires
11	Load wheel size	mm	φ457×178
12	Drive wheel size	mm	φ415×178
13	Number of wheels,front/rear(x=drive wheel)		2x/2
14	Wheel base drive side	b10(mm)	800
15	Wheel base, load-bearing side	b11(mm)	1090
16	Tilt of fork, Forward/Backward	α/β(°)	1/3
17	Mast rotation angle	(°)	210°
18	Mast closed height	h1(mm)	3385
19	Free lift height	h2(mm)	1700
20	Lift height	h3(mm)	6320
21	Height of mast open	h4(mm)	7500
22	Overhead guard height	h6(mm)	2250
23	Seat height	h7(mm)	1230
24	Overall length	L1(mm)	3830
25	Length to fork face	L2(mm)	2730
26	Overall width	b1/b2(mm)	980/1260
27	Fork size	l/e/s(mm)	1100/100/50
28	Installation level		II
29	Fork rack width	b3(mm)	990
30	Fork outside width	b5(mm)	250~890
31	Lateral displacement	mm	±100
32	Mast ground clearance	m1(mm)	70
33	Body ground clearance	m2(mm)	100
34	Aisle width (pallet 800x1200)Load center	Ast(mm)	1900
35	Minimum main aisle width(pallet 1000*1200depth)	(mm)	2000
36	Turning radius	Wa(mm)	2200
37	Driving speed, load/unloaded	km/h	13
38	Lifting speed,load/unloaded	mm/s	400/420
39	Lowering speed,load/unload	mm/s	280/200
40	Maximum climbing capacity,full loaded/no	%(tanθ)	12/13
41	Braking mode	,,	Mechanical hydraulic
42	Drive motor power (S2-60min)	kw	AC18.5
43	Lift motor power, (S3-15%)	kw	AC15
44	Battery, voltage/rated capacity	V/Ah	48/900
45	Battery weight	kg	1400
46	steering system	1.3	Hydraulic



















Call Us: 1300 000 168 Email: sales@jialift.com.au