

# JIALIFT®



[www.jialift.com.au](http://www.jialift.com.au)

## E1240GL COUNTERBALANCE STACKER

CE

- 1200kg Capacity
- Maximum Lift Height: 4000mm
- Safe, reliable, sustainable and low maintenance

# JIALIFT®

## MATERIAL HANDLING EQUIPMENT

Model		E1030GL	E1330GL	E1240GL
Power unit		电动(Electric)		
Operation		PEDESTRIAN		
Rated traction weight	Q (kg)	1000	1300	1500
Load centre	c (mm)	600MM		
Axle centre to fork face	x (mm)	150		
Wheel base	y (mm)	1203	1203	1330
Service weight with battery	kg	1560	1760	1860
Wheels type				
		聚氨酯 (PU)		
Driving wheel size	Φ × w(mm)	Φ250 × 75		
Bearing wheel size	Φ × w(mm)	Φ250 × 120		
Wheels, number front/rear (x = driven)		2/1 x		
Track width	b10 (mm)	886		
Track width	b11 (mm)	0		
Mast/fork carriage tilt, forward/backward				
	a/b (°)	2/5		
Height of mast, lowered	h1 (mm)	1995		
Free lift	h2 (mm)	100		
Lift	h3 (mm)	3000		
Height of mast, extended	h4 (mm)	4100		
Height of seat/stand-on platform	h7 (mm)	127		
Overall height(With handle)	h14 (mm)	1105/1440		
Lowered fork height	h13 (mm)	40		
Overall length	l1 (mm)	2538	2665	
Length to fork face	l2 (mm)	1588	1715	
Overall width	b1/ b2 (mm)	814/998		
Fork dimensions	s/e/l (mm)	35/100/950		
Width of fork carriage	b3 (mm)	220/720		
Width of forks	m1 (mm)	90		
Min.Ground clearance	m2 (mm)	86		
Aisle width with pallet 1000 x 1200 across forks	Ast (mm)	2945	3067	
Aisle width with pallet 800 x 1200 along forks	Ast (mm)	3055	3177	
Min.Turning radius	Wa (mm)	1445	1570	
Travel speed,laden/unladen				
	(km/h)	5.2/5.5		
Lifting speed, with/without load				
	(mm/s)	100/120		
Lowering speed, with/without load				
	(mm/s)	130/120		
Maximum climbing ability, with/without load				
	(%)	6/8		
Service brake		电磁制动(Electromagnetic)		
Drive motor, 60 minute rating				
	(kW)	1.7		
Lift motor rating at S3 15%				
	(kW)	2.2		
Battery voltage/rated capacity				
	(V/Ah)	24/210		
Battery weight ( ± 5%)				
	(kg)	190		
Type of drive control				
		交流速度控制(AC)		
Noise level at operator 's ear				
	(dB(A))	≤ 75		
Type of steering				
		电子助力(Electric)		



JIALIFT AUSTRALIA PTY LTD

Call Us: 1300 000 168 Email: sales@jialift.com.au

www.jialift.com.au