

## E1030J

### Counterbalance Walkie Stacker

- High ground clearance and large load wheels for comfortable travel on uneven ground.
- No license required to operate
- Single phase in-built intelligent charger ensures comfortable and reliable charging at any standard single phase wall socket.
- Slow and fast drive speed switch, Belly button reversing switch
- Ergonomically designed butterfly-type speed control allow users to operate the E07 using the forward and reverse butterfly control for precise manoeuvring and easy access of the lift/ lower functions for both left and right-handed operators.
- Pedestrian controlled walkie stacker which has no straddle legs
- Allows operators to work in narrow spaces and can be used wherever support arm stacker cannot operate



### E1030J

Specifications		
Model designation		E1030J
Load capacity	kg	600
Load capacity on max. Height	kg	400
Max lifting height	mm	3000
Load centre distance	mm	600
Weight		
Service weight	kg	1430
Dimensions		
Fork length	mm	1150
Single fork width	mm	100
Overall fork width	mm	220-640
Lowered fork height	mm	60
Turning radius	mm	1175
Overall length	mm	2086
Overall width	mm	878
Extended mast height	mm	3533
Lowered mast height	mm	2053
Performance data		
Driving speed, laden/ unladen	km/ h	4.2
Lifting speed, laden/ unladen	mm/ s	95/160
Lowering speed, laden/ unladen	mm/ s	125/98
Electric-engine		
Drive motor rating	kW	0.75
Lift motor rating	kW	2.2
The charger		10A
Battery voltage/nominal capacity		2 x 12V/100Ah
Battery Weight	kg	2 x 27



## E1030J

