

# JIALIFT®



[www.jialift.com.au](http://www.jialift.com.au)

## Q1550GA Reach Stacker

CE

- Reach, tilt function, power steering
- Easy to operate, no forklift license required
- Safe, reliable, sustainable and low maintenance

## JIALIFT Walkie Reach Stacker

The Q1550GA is a pedestrian controlled reach stacker which has a reach function suitable for operators that don't have forklift licenses.

For exceptional productivity and work efficiency in your material handling applications, the Q Series gives you a good combination of power, flexibility, and operator comfort. It offers a number of **advantages**:

- High ground clearance and large load wheels for comfortable travel on uneven ground.
- No license required to operate
- Single phase in-built intelligent charger ensures comfortable and reliable charging at any standard single phase wall socket.
- Slow and fast drive speed switch, Belly button reversing switch
- Reach and tilt function, micro switch and power steering; Free lifting until 1.5m
- Ergonomically designed butterfly-type speed control allow users to operate the Q12 series using the forward and reverse butterfly control for precise maneuvering and easy access of the lift/ lower functions for both left and right-handed operators.

### Standard Equipment:

Also Included in our Offer: Battery and Charger

Warranty: up to 5 Years refer to the JIALIFT warranty terms and conditions



**JIALIFT AUSTRALIA PTY LTD**

Call Us: 1300 000 168 Email: [sales@jialift.com.au](mailto:sales@jialift.com.au)

[www.jialift.com.au](http://www.jialift.com.au)

# JIALIFT®

## MATERIAL HANDLING EQUIPMENT

Manufacturer	JIALIFT
Model	Q1550GA
Max Capacity	1400KG
Operation	PEDESTRIAN
Rated traction weight	2000
Load centre	500
Mast Type	3 STAGE MAST
Axle centre to fork face	324
Wheel base	1554
Service weight	3020
Wheels type	POLYURETHANE
Driving wheel size	Φ250×127 (PU)
Bearing wheel size	Φ250×120
Balance wheel size	Φ149×60
Wheels, front/rear	1, 4/2
Wheelbase, driving end	665
Wheelbase, bearing end	976
Mast carriage tilt,	3/5
Height of mast, lowered	2357
Free lift height	1470
Lift height	5000
Height of mast extended	5920
Operating position handle lever min/max height	1075/1502
Min.Ground clearance	40



**JIALIFT AUSTRALIA PTY LTD**

Call Us: 1300 000 168 Email: sales@jialift.com.au

[www.jialift.com.au](http://www.jialift.com.au)

# JIALIFT®

## MATERIAL HANDLING EQUIPMENT

Overall length	2530/2942
length to fork face	1460/1872
Overall width	940/1106
Fork dimensions	40/120/1070
Width of forks	240-715
Distance between support arm and load surface	746
Forward distance	500
Min.Ground clearance	48
Aisle width with pallet 1000x1200 across forks	2900
Aisle width with pallet 800x1200 along forks	2960
Turning radius (pedal fold/pedal expand)	1800/2205
Traveling speed,laden/unladen	5.2/5.5
Lifting speed,laden/unladen	130/180
Lowering speed,laden/unladen	160/210
Forward speed,laden/unladen	80/85
Max.climbing ability, laden/unladen	6/8
service brake	ELECTROMAGNETIC
Drive motor	2.5
lifting motor rating	4.5
Battery	no
Battery voltage/rated capacity	24/280
Battery weight (±5%)	275
Type of Drive control	AC SPEED CONTROL
Noise level	≤75



**JIALIFT AUSTRALIA PTY LTD**

Call Us: 1300 000 168 Email: sales@jialift.com.au

[www.jialift.com.au](http://www.jialift.com.au)